

MYRICA V27-1 LCD TV

Issue Mai 2005

Pages 2

So versatile, so refined: the 27" MYRICA LCD TV is the perfect enhancement of your living room, bedroom or home office. Enjoy the stunning image quality for your favorite movie, or connect it to your PC for true multimedia performance.
27" (68 cm) LCD screen with 900:1 contrast for an exceptional picture. HD ready, for tomorrow's high-end TV content. 1280 x 720 resolution makes the most of movies and television. Enjoy excellent audio fidelity with integrated stereo speakers. Progressive scan technology delivery stunning image quality.

- 27 inch wide screen LCD TFT display
- High resolution 1280 x 720 pixels
- 16.7 Mio colours
- Viewing angle 176°/ 176°
- High brightness 550 cd/m² and enormous contrast (900:1)
- Multi norm TV tuner (PAL/SECAM)
- Multiple video inputs
- Teletext (256 pages)
- Plug and Play DDC 2B interface
- Immune to external electromagnetic fields
- Analogue (D-Sub) input and DVI-D with HDCP support
- 8 languages OSD menu
- Country specific warranty
- HD ready
- 8 ms response time



Visible screen diagonal	27 inch (68 cm) wide
Panel resolution	
pixels	1280 x 720
Picture size	597.12 x 335.88 mm
Brightness typical	550 cd/m ²
Contrast typical	900:1
Viewing angle typical	
Horizontal	176°
Vertical	176°
Response time g/g avg	8 ms
Options	
TV tuner	VHF/UHF/cable
Standard	B/G, D/K, I and L/L' (Multi Europe)
System	PAL / SECAM
Sound system	mono, stereo, dual tone
Teletext	256 pages (FLOF/TOP)
Video I/O	
TV-RF In	IEC-connect
DVI-D	with HDCP support
D-SUB	15pin
AV1 (In)	Component Video (YPbPr)
AV2 (In/Out)	21-pin Scart
AV3 (In/Out)	21-pin Scart
S-Video In	(4 pin Dim)
Composite video	RCA type
PC (input)	
D-Sub	
DVI-D with HDCP support	
Horizontal frequency	31.15 – 64 kHz
Vertical frequency	56 – 75 Hz
Resolutions	1280 x 1024 60 Hz
	1280 x 720 60 Hz
	1024 x 768 60 - 75 Hz
	800 x 600 56 - 75 Hz
	640 x 480 60 - 75 Hz
	640 x 350 70 Hz
Video	480i, 480p, 576i, 576p, 720p, 1080i with HDCP
Audio characteristics	
Volume control	digital
PC audio (In)	3.5 mm stereo phone jack
6 x RCA (In)	Video, S-Video, Component
Earphone (Out)	3.5 mm stereo phone jack
Sub woofer (Out)	RCA pin
Sound output	5 W (L) + 5 W (R)

Electrical values

External AC adapter	
Rated voltage	100-240 V
Frequency	50-60 Hz
Power draw	
Operating typical	115 W
Standby mode	< 8 W
Protection class	1

Temperatures/dimensions/weight

Ambient temperature (to IEC721)	
Recommended range	15°C to 35°C
Limit	5°C to 35°C
Dimensions incl. stand (H x W x D)	520 x 680 x 240 mm
Weight	approx. 15,2 kg (unpacked)

Reliability

MTBF (demonstrated)	50,000 h
Lifetime of backlight (brightness > 50 % of original brightness)	50,000 h

Compliance with standards

Product safety	EN60950 + IEC guide 112
Ergonomics	GS mark
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55013, EN55020B, EN55022/B, EN55024, 61000-3-2/-3)

Accessories

Power cable (1.8 m)	for wall socket Euro-Schuko-Type CEE7 plug type IEC-320-C13 incl. batteries (2x AAA)
Remote control	incl. batteries (2x AAA)
User manual	multi language

Special features

PIP (Picture-In-Picture)	
Automatic program search	

Order code	S26361-K1036-V170
-------------------	-------------------

EAN	4045827314349
------------	---------------